



Minimatic slip-on fittings provide a flexible, easy alternative to ferrule and push-to-connect design fittings.

Clippard Minimatic slip-on fittings are designed to be used with Clippard urethane hose. The flexibility and strength of urethane hose and the compact design of the fittings are ideal for pneumatic applications where convenience and size are considerations. The Minimatic slip-on fitting used with Clippard urethane hose will provide a leak free connection that will hold well beyond the working pressure of the hose without the need for additional clamps.













Minimatic slip-on fittings are available in a wide variety of

configurations in a number of styles including tee, connectors, crosses, swivel, and universal. Barb sizes can be mixed on the same fitting for applications requiring multiple tubing sizes. The electroless nickel plating of Minimatic slip-on fittings provides corrosion resistance in applications involving high moisture, while enabling the fittings to retain their original, lustrous appearance. Buna-N gasket included with #10-32 threads except when ordered in bulk.













### Features

- Single barb design for quick and easy positive seal
- Miniature size provides low profile
- Multiple configurations for every need
- Brass Electroless nickel plating
- Available with 1/16", 3/32" or 1/8" hose barb
- Available with #10-32 thread and 1/8" NPT
- Holds to the burst pressure of polyurethane hose

## CONNECTOR FITTINGS

<b>C22</b> 	 <p>(2) 1/16" I.D. hose barb 0.656 1/4" sq.</p>	<b>C32</b> 	 <p>3/32" I.D. hose barb 0.684 1/4" sq. 1/16" I.D. hose barb</p>	<b>C33</b> 	 <p>(2) 3/32" I.D. hose barb 0.712 1/4" sq.</p>
<b>C42</b> 	 <p>1/16" I.D. hose barb 0.750 1/4" sq. 1/8" I.D. hose barb</p>	<b>C43</b> 	 <p>3/32" I.D. hose barb 0.762 1/4" sq. 1/8" I.D. hose barb</p>	<b>C44</b> 	 <p>0.875 1/4" hex. (2) 1/8" I.D. hose barb</p>

## #10-32 to Hose Connectors

<b>CT2</b> 	<p>Gasket comes pre-installed</p>  <p>1/16" I.D. hose barb 0.468 1/4" hex. #10-32 thd.</p>	<b>CT3</b> 	<p>Gasket comes pre-installed</p>  <p>3/32" I.D. hose barb 0.523 1/4" hex. #10-32 thd.</p>	<b>CT4</b> 	<p>Gasket comes pre-installed</p>  <p>1/8" I.D. hose barb 0.562 1/4" hex. #10-32 thd.</p>
<b>CT0-2</b> 	<p>Gasket included. Not installed</p>  <p>1/4" sq. 0.468 1/16" I.D. hose barb #10-32 thd.</p>	<b>CT0-3</b> 	<p>Gasket included. Not installed</p>  <p>1/4" sq. 0.468 0.493 3/32" I.D. hose barb #10-32 thd.</p>	<b>CT0-4</b> 	<p>Gasket included. Not installed</p>  <p>1/4" sq. 0.468 0.562 1/8" I.D. hose barb #10-32 thd.</p>