

Square and rectangular pressure gauges PPB Series



- Square and rectangular case
- Measuring range : 0...+60 bar
- Square 72x72 / 96x96 / 144x144
- Rectangular 72x144 / 144x72

APPLICATIONS

Square or rectangular pressure gauges, PPB series, are intended for general industrial and pneumatic applications.

TECHNICAL DETAILS

Measuring range	0 à 60 bar
Accuracy class	1,6 for 72x72 1 for 96x96, 144x144, 72x144 and 144x72
Pressure element	C tube, brass for model 72x72 and 96x96 C tube, AISI 316 L for other model
Movement	Brass or AISI 304, see table
Case	ABS, black noryl
Window	Plexiglass
Socket, connection	Brass or AISI 316 Ti, G1/4" female
Fixation	Panel mounting
Protection	IP 45
Operating temperature	-30°C à 150°C

REFERENCES

Square type, G 1/4" Female, Brass or AISI 316 Ti

Measuring range	72 x 72	96 x 96	144 x 144
	Brass	Brass	AISI 316 Ti
0 1 bar	880 100	880 110	880 120
0 1,6 bar	880 101	880 111	880 121
0 2,5 bar	880 102	880 112	880 122
0 4 bar	880 103	880 113	880 123
0 6 bar	880 104	880 114	880 124
0 10 bar	880 105	880 115	880 125
0 16 bar	880 106	880 116	880 126
0 25 bar	880 107	880 117	880 127
0 40 bar	880 108	880 118	880 128
0 60 bar	880 109	880 119	880 129

Rectangular type, G 1/4" Female, AISI 316 Ti

Measuring range	Bottom	Back connection
	72 x 144	144 x 72
0 1 bar	880 130	880 140
0 1,6 bar	880 131	880 141
0 2,5 bar	880 132	880 142
0 4 bar	880 133	880 143
0 6 bar	880 134	880 144
0 10 bar	880 135	880 145
0 16 bar	880 136	880 146
0 25 bar	880 137	880 147
0 40 bar	880 138	880 148
0 60 bar	880 139	880 149



8 Av. du Gué Langlois · 77600 Bussy-Saint-Martin
Tel +33 (0)1 60 37 45 00 Web www.citec.fr
E-mail citec@citec.fr

Square and rectangular
pressure gauges
PPB Series

19-06-2023

D-806.67-EN-AB

PR

806-67 /1